

SP-GJSC-06 8Port Fiber Sealed Drop Closure (FSDC)



1. Product Overview

SP-GJSC-06 Waterproof Fiber Optic Splice Closure is able to hold up to 8 subscribers and 96 splicing points as closure. It is used as a termination point for the feeder cable to connect with drop cable in FTTx network system. It integrates fiber splicing, splitting, distribution, storage and cable connection in one solid protection box.

2. Features:

- Water-proof design with IP-68 Protection level.
- Integrated with flap-up splice cassette and adaptor holder.
- Impact test: IK10, Pull Force: 100N, Full rugged design.
- Maximum 96F splice capacity, stainless anti-rust bolts and nuts.
- Plug- and-play installation, easy for maintenance and expansion.
- Fiber bend radius control more than 40mm.
- 180 degree access with buckled lock structure.
- 1*8 PLC Splitter can be installed in each splice tray as option.
- Mechanical sealing structure and mid-span cable entry.
- 8pcs of pre-installed reinforced OptiTap Compatible adapter for SC.
- 1 mid-span cable entrance(10-16.5mm) for uncut cable.

Shenzhen Spring Optical Communication CO., LTD

WhatsApp: +86-18003542533

www.springoptical.com

Email: Hayden@springoptic.com

3.Configuration:

Material	Size	Max Capacity		Reinforced Adaptor	Weight	Color
Strengthen Polymer Plastic	385*245*130mm	Splice 96 Fibers (4trays,24fiber/tray)	PLC Splitter 1pc of 1X8	8pcs SC/UPC or SC/APC	4.5kg	Black

4. Applications:

- Wall mounting installation
- Pole mounting installation
- Aerial hanging installation
- Suitable for Hardened OptiTap drop cable with reinforced connector

5. Standard Accessories:

Splice cassette and cable management tool, installation nuts and bolts, protection sleeves, hose clamp, cable tube, wrench, cover holder, rubber seal for cable entrance.

6. Optional Accessories:

Pole mounted kits, Aerial hanging kits.

Shenzhen Spring Optical Communication CO., LTD

WhatsApp: +86-18003542533

www.springoptical.com

Email: Hayden@springoptic.com